

## Datasheet

- V23-2100G 12V 100mA Power Supply
- V23-2350 12V 350mA Power Supply
- 12V 100mA Universal Power Supply for most masthead amplifiers
- 12V 350mA Switch-Mode-Power-Supply (SMPS) for Vision XDA and higher current devices
- Ideal power supplies for Vision Gold range of amplifiers
- Thermal cut-out fuse in transformer + short circuit & overload protection
- LED "power on" indicator
- Double sided PCB for reliability and stability
- Fully screened RF loop-through with F-Connectors
- 0.6m mains lead with UK mains plug with 3A fuse fitted
- Low insertion loss
- Visible fixing lugs and screw holes for easy fixing



Model	V23-2350	V23-2100G
Outage Voltage	12V-negative earth Centre pin +ve	12V-negative earth Centre pin +ve
Current	350mA	100mA
Insertion Loss	<0.5dB	<0.5dB
Frequency range	5 to 862MHz	5 to 862MHz
RF Connection	F-female for input and output	F-female for input and output
Mains Voltage	230V AC ±10% 50Hz	230V AC ±10% 50Hz
Mains Plug	UK moulded plug with 3A fuse	UK moulded plug with 3A fuse
Lead	0.6m mains lead	0.6m mains lead
Size	106mm x 51mm x 40mm	106mm x 51mm x 40mm
Weight Kg	0.35	0.35
Packing	Individual carton. 18 per outer	Individual carton. 18 per outer
RoHS Compliance	RoHS Compliant. Exempt from WEEE/RoHS directive as at 15/03/07. Intended for professional use as part of a fixed installation only	

In the interests of continued product development & improvement, Vision Products (Europe) Ltd reserves the right to change product specifications, design & dimensions. Data correct at time of going to press.04/08/2008